








FC CART1



DESCRIPTION	Transfer paper for cardboard	
TECHNICAL DATA	FC CART1 is made of a 120 µm, 115 g/m ² paper liner , a 30 µm, a 25 g/m ² polyethylene layer and a 3 µm composite polymer finish .	
EQUIPMENT	Color laser printer or copy machine + heat press	
SUITABLE FOR	Ideal for cardboard calendar heads	

FEATURES

FC CART1 has an **attractive semiglossy look** and doesn't change the material's original feel. **Gives great colors.**

INSTRUCTIONS	1 	Insert the transfer paper in the printer's by-pass or drawer and set to extra heavy printing mode (approx. 160 g/m ²). Multicopy print. Print in mirror mode.
	2 	Place the printed side of the FC CART1 transfer paper on the cardboard surface (in the centre of the plate).
	3 	Place a sheet of adhesive-proof tissue paper (AU CFC VELIN) beneath and above the cardboard. Then: Air press: 150°C for 20-25"- pressure 4atm Manual press: 150°C for 20-25"- medium-high pressure
	4 	Cold peel off

WARNINGS	If the transfer paper doesn't come off, lower time and temperature. If parts of color are missing increase time and temperature. These settings may vary depending on type of cardboard. For more information please contact your dealer.	STORAGE	Store in a cool dry place. Do not expose to direct sunlight. If properly stored the product will maintain its features for at least 2 years.
----------	---	---------	--

The instructions on this sheet are merely indicative and contain details concerning tests carried out in our laboratories with our equipment. Do your own testing. The manufacturer will replace defective material but is not responsible for any damage resulting from incorrect use.

* Also available in 100/A4 sheets packages

SHOCKLINE
about your transfer paper

T. +39 (0)875 751194 - F. +39 (0)875 751329
info@shockline.it - skype shock.line
www.shockline.it - www.digidecor.it

code