



FO PRIPEL



DESCRIPTION	Transparent primer for FC FILM2 transfer paper	
TECHNICAL DATA	FO PRIPEL is made of a 120 µm, 115 g/m ² paper liner , a 25 g/m ² , 30 µm polyethylenic layer and a 8 g/m ² protective polyurethane layer .	
EQUIPMENT	Heat press or laminator	
SUITABLE FOR	Ideal combined with FC FILM2 for custom printing on many light colored materials such as leather, leatherette, wood, cardboard, cork and canvas.	FO PRIPEL is a trasparente primer which provides improved adhesion on difficult light colored surfaces .

FEATURES

INSTRUCTIONS		1 After printing FC FILM2, place the glossy side of FO PRIPEL on the printed side of the transfer paper and lamine with a heat press or laminator.
		2 Laminator: approx 130°C - speed 1
		2 Protect the laminated papers FC FILM2+FO PRIPEL with a soft silicone mat (MA STUOI GB80-2). Then: Air press: 140°C for 40" - pressure 5atm Manual press: 140°C for 40" - high pressure N.B.: If no silicon pad is used, lower pressing times
		3 Wait until it cools down and remove the paper liner from the FO PRIPEL . Continue as indicated on the FC FILM2 instructions (points 2 to 6).

WARNINGS	For materials with poor heat resistance press at approx. 100°C . For further information contact your dealer.	Store in a cool dry place. Do not expose to direct sunlight. If properly stored the product will maintain its features for at least 2 years.	STORAGE
----------	--	--	---------

The instructions on this sheet are merely indicative and contain details concerning tests carried out in our laboratories with our equipment. Do your own testing. The manufacturer will replace defective material but is not responsible for any damage resulting from incorrect use.

* Also available in 100/A4 packages

SHOCKLINE
about your transfer paper

T. +39 (0)875 751194 - F. +39 (0)875 751329
info@shockline.it - skype shock.line
www.shockline.it - www.digidecor.it

code